



PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

Issue date: 9 March 2022 Revision date: 9 March 2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : PRO HD 2500 XE
Product code : 15448, 15452, 15464, 25205, 25206, 30203, 35202XE, 40202XE, 45202XE, 99901

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Tire Additive, Tire sealant; Tire Flat Preventative

1.3. Supplier

Manufacturer:
MULTI SEAL
18918 Phillip Way
New Caney TX 77357
USA
T: 1-800-577-3353(24hrs)
E: info@multiseal.us

1.4. Emergency telephone number

Emergency number : 1-800-577-3353 (24hrs)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4

Specific target organ toxicity (repeated exposure) Category 2

Harmful if swallowed

May cause damage to organs through prolonged or repeated exposure

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

Harmful if swallowed

May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands, forearms and face thoroughly after handling.

Do not eat, drink or smoke when using this product.

If swallowed: Call a poison center or doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Rinse mouth.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Ethylene glycol	CAS-No.: 107-21-1	35 – 55	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash with water and soap as a precaution. Seek medical attention if ill effect or irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if ill effect or irritation develops.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May be harmful if swallowed.
------------------	---

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: On combustion, forms: carbon oxides (CO and CO ₂).
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent entry to sewers and public waters.

6.1.1. For non-emergency personnel

Protective equipment : No special protection required.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : No special protection required.

Emergency procedures : No special requirements.

6.2. Environmental precautions

Avoid discharge to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Take up liquid spill into inert absorbent material. In case of large spillages: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Collect spillage. Wipe up with absorbent material (for example cloth). Store away from other materials.

Other information : Dispose in a safe manner in accordance with local/national regulations.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Read label before use. Observe the label precautions. Keep out of reach of children.

Hygiene measures : Observe the label precautions. Do not eat, drink or smoke when using this product. Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed in a cool, well-ventilated place. Keep container closed when not in use. Store in a well-ventilated place.

Incompatible materials : Strong oxidizing agents. Strong acids. Strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PRO HD 2500 XE

No additional information available

Ethylene glycol (107-21-1)

USA - ACGIH - Occupational Exposure Limits

Local name	Ethylene glycol
ACGIH OEL TWA [ppm]	25 ppm (vapor fraction)

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

Ethylene glycol (107-21-1)	
ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH OEL STEL [ppm]	50 ppm (vapor fraction)
ACGIH OEL Ceiling	100 mg/m ³
ACGIH OEL Ceiling [ppm]	39.4 ppm
Remark (ACGIH)	H
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2022
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL C [ppm]	50 ppm
Monitoring methods	
Monitoring methods	No additional information available.

8.2. Appropriate engineering controls

Appropriate engineering controls : Not required for normal conditions of use. Normal use of this product shall imply use in accordance with the instructions on the packaging.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Not required for normal conditions of use. Normal use of this product shall imply use in accordance with the instructions on the packaging.

Hand protection:

No special protection required. In case of repeated or prolonged exposure : Impermeable protective gloves.

Eye protection:

No special protection required

Respiratory protection:

No special protection required

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Heterogenous Mixture

Appearance : Gel. Viscous.

Color : Red/Pink

Odor : Odorless

Odor threshold : No data available

pH : 8 – 10

Melting point : -35 °C (-31 °F)

Freezing point : No data available

Boiling point : > 100 °C (212 °F)

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.1 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. On combustion, forms: carbon oxides (CO and CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

PRO HD 2500 XE	
ATE US (oral)	1 g/kg body weight
Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

Ethylene glycol (107-21-1)	
LD50 dermal rat	10600 mg/kg
LC50 Inhalation - Rat	> 2.5 mg/l (Exposure time: 6 h)
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	10600 mg/kg body weight

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 8 – 10
Serious eye damage/irritation	: Not classified (Based on an assessment of exposure risk, finished product is not classified) pH: 8 – 10
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

Ethylene glycol (107-21-1)	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic	: No data available
Symptoms/effects	: May cause damage to organs through prolonged or repeated exposure. May be harmful if swallowed.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol (107-21-1)	
LC50 - Fish [1]	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

12.2. Persistence and degradability

PRO HD 2500 XE	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

PRO HD 2500 XE	
Bioaccumulative potential	Not established.

Ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Pow)	-1.93

12.4. Mobility in soil

No additional information available

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

PRO HD 2500 XE

Safety Data Sheet

according to US HazCom 2012

15.3. US State regulations



WARNING:

This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to US HazCom 2012

Revision date

: 9 March 2022

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.